



Laser Diode ZBD-LD-525-2100M-FX-MC

ZBD-LD-525-2100M-FX-MC is a multimode laser diode with 2.1 W CW output power at 525nm. Its beam pattern is linear with $11^\circ \times 1^\circ$ ($\theta_{//} \cdot \theta_{\perp}$). It is supplied in a 9mm floating mounted TO can with Zener Diode. The laser diode is suitable for opto-electronic applications..

■ Absolute Maximum Ratings

Item	Symbol	Absolute Maximum Rating	Unit
Forward Current($T_c=25^\circ\text{C}$)	I_f	2.6	A
Revers Current($T_c=25^\circ\text{C}$)	$I_r(\text{LD})$	85	mA
Storage Temperature	T_{stg}	-40~85	$^\circ\text{C}$
Operating Case Temperature	T_c	0~55	$^\circ\text{C}$

■ Initial Electrical/Optical Characteristics ($T_c=25^\circ\text{C}$)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit	
Optical Output Power	P_o	$I_f = 2.4\text{A}$	1.7	(2.1)	2.4	W	
Dominant Wavelength	λ_d	$I_f = 2.4\text{A}$	519	(525)	531	nm	
Threshold Current	I_{th}	CW	170	-	450	mA	
Operating Voltage	V_{op}	$I_f = 2.4\text{A}$	3.7	-	5.4	V	
Slope Efficiency	η	CW	-	(2.6)	-	W/A	
Beam Divergence*	Parallel	$\theta_{//}$	$I_f = 2.4\text{A}$	5	(11)	25	$^\circ$
	Perpendicular	θ_{\perp}	$I_f = 2.4\text{A}$	0.8	(1)	1.2	$^\circ$

()are reference figures.

*Full angle at $1/e^2$ from peak intensity

